Carrier Sliding Door Single Rail x3

Machine guard door

The carrier sliding door with 3 single rails can be built from our mesh or polycarbonate panels to fit your chosen machine guard system. The door is built using the standard panel height of 2050 mm in up to 6 witdhs togehter with either the 60x40 mm or 80x80 mm posts. The panels and posts together with the top rail and door kit are supplied separate for assembly on site.

Depending on the risk assessement, you choose the preferable lock for your door; Cylinder Lock or the Troax Safe Lock built to fit many safety switches.

Maximum opening width as standard option is approximately 4500 mm.

FACTS

Door dimensions, system height 2050 mm	
Panel Option (mm)	**Door Opening Width (mm)**
500+500+500+500	1460
700+700+700+700	2060
800+800+800+800	2360
1000+1000+1000+1000	2960
1200+1200+1200+1200	3560
1500+1500+1500+1500	4460

Standard colour for the 60x40 mm posts are grey RAL7037, black RAL9005 or yelow RAL1018. Standard colour for mesh panels are RAL 7037 and RAL 9005

Doors can be made in the colour of your choice.



LOCK OPTIONS

Cylinder Lock (Kit 5780)

Safe Lock (Kit 5030)

Safe Lock ES (Kit 5040)



201901-2896-UND